

---

---

आई पी 2-एक्स वाली तीन फेज प्रेरण मोटरो की  
कार्यकारिता अभिलक्षण सम्बन्धी मान  
( दूसरा पुनरीक्षण )

**Values of Performance  
Characteristics for Three-Phase  
Squirrel Cage Induction Motors with  
Degree of Protection IP-2X  
( Second Revision )**

ICS 29.160.30

© BIS 2021



भारतीय मानक ब्यूरो  
BUREAU OF INDIAN STANDARDS  
मानक भवन, 9 बहादुरशाह ज़फर मार्ग, नई दिल्ली – 110002  
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG  
NEW DELHI-110002  
[www.bis.gov.in](http://www.bis.gov.in) [www.standardsbis.in](http://www.standardsbis.in)

## FOREWORD

This Indian Standard (Second Revision) was adopted by the Bureau of Indian Standards, after the draft finalized by the Rotating Machinery Sectional Committee had been approved by the Electrotechnical Division Council.

This standard was first published in 1978. First revision of this standard was issued to enlarge the scope by adding 8 pole motors. The value of efficiency of motors was given replacing the earlier value of 'product of efficiency and power factor' in the Tables 1 to 8. This would permit the user to choose the motor with higher efficiency essentially as step towards specifying energy conservation features.

The second revision has been taken up to retain only SPDP squirrel cage induction motor performance with IC01 cooling. The performance for TEFC squirrel cage induction motor is now covered in IS 12615 : 2018 and hence dropped from this standard. The title of this standard has been changed to include motors with IP 21, 22 or 23 protections. The list of referred standards have been updated to include latest standards.

This standard is prepared with a view to cover the values of performance characteristics for three-phase induction motors having output rating up to 37 kW. The motor manufacturer may declare the performance characteristics of motors above 37 kW and these values are subject to tolerances specified in IS 15999 (Part 1).

The full load speed and breakaway torque values indicated in tables are nominal values.

The composition of the Committee, responsible for the formulation of this standard is given at Annex B.

For the purpose of deciding whether a particular requirement of this standard is complied with the final value, observed or calculated, expressing the result of a test or analysis shall be rounded off in accordance with IS 2 : 1960 'Rules for rounding off numerical values ( *revised* )'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

## *Indian Standard*

# VALUES OF PERFORMANCE CHARACTERISTICS FOR THREE-PHASE SQUIRREL CAGE INDUCTION MOTORS WITH DEGREE OF PROTECTION IP-2X

( *Second Revision* )

### 1 SCOPE

This standard covers the performance characteristics of 2, 4, 6 and 8 pole three-phase squirrel cage induction motors with degree of protection IP-2X having output ratings up to and including 37 kW at rated voltage and frequency of 415 V and 50 Hz for continuous duty type  $S_1$ .

### 2 REFERENCE

The standards listed in Annex A contain provisions which through reference in this text, constitute provision of this standard. At the time of publication, the editions indicated were valid. All standards are subjected to revision and parties to agreements based on this standard are encouraged to investigate the possibility of applying most recent editions of the standards.

### 3 TERMINOLOGY

For the purpose of this standard, the definitions given in IS 1885 (Part 35) shall apply.

### 4 OUTPUT RATINGS

This standard covers the values of performance characteristics for the following output ratings:

0.37, 0.55, 0.75, 1.1, 1.5, 2.2, 3.7, 5.5, 7.5, 9.3, 11, 15, 18.5, 22, 30 and 37 kW.

### 5 TYPE OF ENCLOSURES

The values of performance characteristics are applicable for motors having enclosures with degree of protection or IP 21, IP 22 or IP 23 (*see* IS/IEC 60034-5).

### 6 METHODS OF COOLING

This standard covers motors having internal and external cooling methods IC 01 (*see* IS 6362).

### 7 PERFORMANCE VALUES

7.1 The values of the performance characteristics of motors are covered under Tables 1 to 4 as follows:

<i>No. of poles</i>	<i>Type of Enclosures</i>	<i>Methods of Cooling</i>	<i>Table No</i>
2	IP 21, IP 22 or IP 23	IC 01	1
4	IP 21, IP 22 or IP 23	IC 01	2
6	IP 21, IP 22 or IP 23	IC 01	3
8	IP 21, IP 22 or IP 23	IC 01	4

#### NOTES

1 The values of performance characteristics specified in Tables 1 to 4 may not be applicable to motors whose minimum breakaway torque is higher than 180 percent of the full load torque.

2 The minimum breakaway torque values specified for the motor are at room temperature. The other values relating to speed, current, and efficiency apply to the motor when it has attained thermal equilibrium while delivering the rated output.

3 Test procedures for determination of the performance values shall be conducted in accordance with IS 4029.

4 The value of full load current shall be taken as the average value of the currents measured in the three phases.

5 For motors having rated voltage other than 415 V, values given in Tables 1 to 4 shall be applicable except for value of maximum full load current which would be changed in the inverse proportion of the voltage.

6 Tolerance applicable to performance parameters as per IS 15999 (Part 1).

**Table 1 Values of Performance Characteristics of 2-Pole Three-Phase Squirrel Cage Induction Motors Having Enclosures with Degree of Protection IP 21, IP 22 and IP 23 and Method of Cooling IC 01**

( Clause 7.1 )

SI No.	Rated Output kW	Full Load Speed rev/min	Full Load Current, Max A	Breakaway Torque in Terms of Full Load Torque Percent	Efficiency Nominal Percent
(1)	(2)	(3)	(4)	(5)	(6)
i)	0.37	2 720	1.20	170	63
ii)	0.55	2 760	1.60	170	67
iii)	0.75	2 780	2.00	170	71
iv)	1.1	2 790	2.80	170	73
v)	1.5	2 800	3.70	170	76
vi)	2.2	2 810	5.00	170	78
vii)	3.7	2 820	8.00	160	81
viii)	5.5	2 830	11.00	160	82
ix)	7.5	2 840	15.00	160	83
x)	9.3	2 840	19.50	160	82
xi)	11	2 860	23.50	160	83
xii)	15	2 860	31.00	160	84
xiii)	18.5	2 870	38.00	160	84.5
xiv)	22	2 870	44.00	160	85
xv)	30	2 880	57.00	160	85.5
xvi)	37	2 880	70.00	160	86

**Table 2 Values of Performance Characteristics of 4-Pole Three-Phase Squirrel Cage Induction Motors Having Enclosures with Degree of Protection IP 21, IP 22 and IP 23 Method of Cooling IC 01**

( Clause 7.1 )

SI No.	Rated Output kW	Full Load Speed, rev/min	Full Load Current, Max A	Breakaway Torque in Terms of Full Load Torque, Percent	Efficiency Nominal Percent
(1)	(2)	(3)	(4)	(5)	(6)
i)	0.37	1 330	1.40	170	64
ii)	0.55	1 340	1.70	170	69
iii)	0.75	1 360	2.20	170	71
iv)	1.1	1 370	2.90	170	73
v)	1.5	1 380	3.80	170	76
vi)	2.2	1 390	5.10	160	79
vii)	3.7	1 410	8.10	160	83
viii)	5.5	1 420	11.40	160	84
ix)	7.5	1 430	15.40	160	85
x)	9.3	1 430	19.50	160	84
xi)	11	1 430	23.00	160	84.5
xii)	15	1 430	32.00	160	85
xiii)	18.5	1 435	38.50	160	86
xiv)	22	1 440	45.00	160	86.5
xv)	30	1 440	59.00	160	87.5
xvi)	37	1 440	71.00	160	87.5

**Table 3 Values of Performance Characteristics of 6-Pole Three-Phase Squirrel Cage Induction Motors Having Enclosures with Degree of Protection IP 21, IP 22 and IP 23 Method of Cooling IC 01**

( Clause 7.1 )

Sl No.	Rated Output kW	Full Load Speed, rev/min	Full Load Current, Max A	Breakaway Torque in Terms of Full Load Torque, Percent	Efficiency Nominal Percent
(1)	(2)	(3)	(4)	(5)	(6)
i)	0.37	870	1.40	160	63
ii)	0.55	870	1.90	160	65
iii)	0.75	890	2.30	160	68
iv)	1.1	900	3.20	160	71
v)	1.5	900	4.00	160	74
vi)	2.2	910	5.50	150	77
vii)	3.7	920	8.80	150	79
viii)	5.5	920	12.70	150	81
ix)	7.5	920	17.5	150	80
x)	9.3	925	22.00	140	80.5
xi)	11	925	24.0	140	83.0
xii)	15	930	32.5	140	84
xiii)	18.5	935	39.0	140	85.5
xiv)	22	940	45.0	140	86
xv)	30	945	60.0	140	86.5
xvi)	37	950	73.0	140	87

**Table 4 Values of Performance Characteristics of 8-Pole Three-Phase Squirrel Cage Induction Motors Having Enclosures with Degree of Protection IP 21, IP 22 and IP 23 Method of Cooling IC 01**

( Clause 7.1 )

Sl No.	Rated Output kW	Full Load Speed, rev/min	Full Load Current, Max A	Breakaway Torque in Terms of Full Load Torque, Percent	Efficiency Nominal Percent
(1)	(2)	(3)	(4)	(5)	(6)
i)	0.37	640	1.5	150	60
ii)	0.55	640	2.1	150	65
iii)	0.75	650	2.7	150	68
iv)	1.1	660	3.5	150	70
v)	1.5	670	4.5	150	72
vi)	2.2	680	6.10	140	74
vii)	3.7	680	10	140	74
viii)	5.5	680	14.6	140	76
ix)	7.5	685	19.5	140	78
x)	9.3	690	24.0	140	79.5
xi)	11	690	27	140	81
xii)	15	695	36	140	82.5
xiii)	18.5	695	46	130	84
xiv)	22	700	53	130	85
xv)	30	700	71	130	86
xvi)	37	700	87	130	87

**ANNEX A**

( Clause 2 )

**LIST OF REFERRED INDIAN STANDARDS**

<i>IS No.</i>	<i>Title</i>	<i>IS No.</i>	<i>Title</i>
1885 (Part 35) : 1993	Electrotechnical vocabulary: Part 35 Rotating machines	15999 (Part 1) : 2016/ IEC 60034-1 : 2010	Rotating electrical machines: Part 1 Rating and performance ( <i>first revision</i> )
4029 : 2010	Guide for testing three phase induction motors ( <i>first revision</i> )	IS/IEC 60034 (Part 5) : 2000	Rotating electrical machines: Part 5 Degrees of protection provided by the integral design of rotating electrical machines (IP code) — Classification ( <i>second revision</i> )
6362 : 1995	Designation of methods of cooling of rotating electric machines ( <i>first revision</i> )		

**ANNEX B***( Foreword )***COMMITTEE COMPOSITION**

Rotating Machinery Sectional Committee, ETD 15

<i>Organization</i>	<i>Representative(s)</i>
Bharat Heavy Electricals Limited, Bhopal	SHRI ANISH VARSHNEY ( <b>Chairman</b> )
ABB, Ltd, Faridabad	SHRI SWAPAN SARKAR SHRI SUMIT TYAGI ( <i>Alternate</i> )
All India Electrical motor Association, Gujrat	SHRI SANJAY P. JADIA
Best Engineers Pumps Pvt Limited, Coimbatore	SHRI J. GOWRISANKAR
Bureau of Energy Efficiency, New Delhi	SHRI SAMEER PANDITA MS DEEPSHIKHA WADHWA ( <i>Alternate</i> )
Bharat Bijlee Ltd, Mumbai	SHRI SALIL KUMAR MRS ANJALI RANADE ( <i>Alternate</i> )
Bharat Heavy Electricals Ltd, Bhopal	SHRI NISHEETH KHARE SHRI BABOO SONWANE ( <i>Alternate</i> )
Central Electricity Authority, New Delhi	SHRI H. R. ARORA SHRI DEEPAK SHARMA ( <i>Alternate</i> )
Chief Electrical Inspectorate, Tamil Nadu	SHRI N. THIRUVAZHI MARPHA SHRI M. SADASIVAN ( <i>Alternate</i> )
Consumer Education and Research Centre, Gujrat	SHRIMATI SHWETA MAHAJAN
C G Power & Industrial Solutions Ltd, Mumbai	SHRI A. SUDHAKARAN SHRI DILIP PAWAR ( <i>Alternate</i> )
Development Commissioner Micro, Small & Medium Enterprises, New Delhi	SHRI S. K. SAHOO SHRI DHANENDRA PRASAD ( <i>Alternate I</i> ) SHRI S. K. SAINI ( <i>Alternate II</i> )
Electrical Research & Development Association, Gujrat	SHRI R. P. SINGH DR S. H. CHETWANI ( <i>Alternate</i> )
Havell's India Pvt Ltd, Noida	SHRI NIRANJAN SINGHVI
International Copper Association Ltd, Mumbai	SHRI ABHISHEK DHUPAR SHRI D. GOSWAMI ( <i>Alternate</i> )
IEEMA, New Delhi	SHRI ASHOK KULKARNI SHRI VIVEK ARORA ( <i>Alternate</i> )
Indian Institute of Technology, New Delhi	PROF S. S. MURTHY
Indian Pump Manufacturers, Association, Mumbai	SHRI BHARAT B. PATEL SHRI UTKARSH A. CHHAYA ( <i>Alternate</i> )
Ingersoll Rand India Limited, Ahmedabad	SHRI NILESH VORA
Integrated Electric Co (P) Ltd, Gurugram	DR PRAVEEN VIJAYRAGVAN
In Personal Capacity	SHRI DILIP BHAVE
KSB Pumps Ltd, Pune	SHRI RAJESH B. GOTE SHRI SANJEEV CHOUDHARY ( <i>Alternate</i> )
Marathon Electric Motors (India) Ltd, Telangana	SHRI RAJIV RANJAN

<i>Organization</i>	<i>Representative(s)</i>
M N Dastur, Kolkata	SHRI S. SAMPATH SHRI K. B. VENKATESWARA RAO ( <i>Alternate</i> )
Ministry of Defence, New Delhi	SHRI B. N. GURUPRASAD SHRI P. RAJKUMAR ( <i>Alternate</i> )
Nuclear Power Corporation of India Limited, Mumbai	SHRI GEORGE SEBASTIAN SHRI SANJEEV KUMAR TIWARI ( <i>Alternate</i> )
National Test House, Mumbai	SHRI K. N. MISRA SHRI K. MOHANAN ( <i>Alternate</i> )
NTPC Ltd, New Delhi	SHRI HIRDESH GUPTA SHRI RAJESH SHARMA ( <i>Alternate</i> )
Steel Authority of India Ltd, New Delhi	SHRIMATI MADHUPRIYA SHRI V. K. PAL ( <i>Alternate I</i> ) SHRI GULSHAN KUMAR ( <i>Alternate II</i> )
South India Engineering Mfrs Association, Coimbatore	SHRI V. KRISHNAKUMAR
Siemens Limited, Mumbai	SHRI PRASAD HARDIKAR SHRI ASHISH SHERE ( <i>Alternate</i> )
Scientific and Industrial Testing and Research Centre, Coimbatore	SHRI K. GUNABAL SHRI A. M. SELVARAJ ( <i>Alternate</i> )
SJVN, Himachal Pradesh	SHRI R. P. SINGH SHRI R. K. BANSAL ( <i>Alternate</i> )
Testing Electrical Standards Lab, Gandhinagar	SHRI L. S. SHARMA
Thyssen Krupp Industries (India) Pvt Ltd, Mumbai	MS CHARUTA VIKRAM MULAY SHRI VAJNATH G. SANGEKAR ( <i>Alternate</i> )
TMEIC Industrial Systems India Private, Karnataka	SHRI VIJAY KHANDWEKAR
BIS Directorate General	MS PRITI BHATNAGAR, SCIENTIST 'F' AND HEAD (ETD) [REPRESENTING DIRECTOR GENERAL ( <i>Ex-officio</i> ) ]

*Member Secretary*  
MS NEHA AGARWAL  
SCIENTIST 'C' (ETD), BIS





## Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act, 2016* to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

### Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

### Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Catalogue' and 'Standards: Monthly Additions'.

This Indian Standard has been developed from Doc No.: ETD 15 (14666).

### Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

## BUREAU OF INDIAN STANDARDS

### Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002  
Telephones: 2323 0131, 2323 3375, 2323 9402

Website: [www.bis.gov.in](http://www.bis.gov.in)

### Regional Offices:

	Telephones
Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg NEW DELHI 110002	{ 2323 7617 2323 3841
Eastern : 1/14 C.I.T. Scheme VII M, V.I.P. Road, Kankurgachi KOLKATA 700054	{ 2337 8499, 2337 8561 2337 8626, 2337 9120
Northern : Plot No. 4-A, Sector 27-B, Madhya Marg CHANDIGARH 160019	{ 265 0206 265 0290
Southern : C.I.T. Campus, IV Cross Road, CHENNAI 600113	{ 2254 1216, 2254 1442 2254 2519, 2254 2315
Western : Manakalaya, E9 MIDC, Marol, Andheri (East) MUMBAI 400093	{ 2832 9295, 2832 7858 2832 7891, 2832 7892

**Branches :** AHMEDABAD. BENGALURU. BHOPAL. BHUBANESHWAR. COIMBATORE.  
DEHRADUN. DURGAPUR. FARIDABAD. GHAZIABAD. GUWAHATI.  
HYDERABAD. JAIPUR. JAMMU. JAMSHEDPUR. KOCHI. LUCKNOW.  
NAGPUR. PARWANOO. PATNA. PUNE. RAIPUR. RAJKOT. VISAKHAPATNAM.

Published by BIS, New Delhi